

HYDRONIC RADIANT CENTER

IN-FLOOR HEATING SYSTEM

Radiant Heating Made Simple!

- Compact Size
- Flexible with Sizes from 3 to 23 kW
- Pressure Tested to Eliminate Call Backs
- Temperature Range up to 190° F
- Fully Modulating
- Stainless Steel Tank
- Low Pumping Resistance
- Load Management Control Connections
- Redundant Safety Features
- ASME H Stamp and CSA Approved
- HRC Panel and Components – 2 Year Warranty



For your comfort and savings.




RMS/HRC
Radiant Made Simple

75 W Veum Ave.
Appleton, MN 56208
(320) 297-9100

RADIANTMADESIMPLE.COM

HYDRONIC RADIANT CENTER

IN-FLOOR HEATING SYSTEM

FIVE SIMPLE STEPS:

1. Mount the HRC Panel on the wall
2. Connect to the radiant floor manifold system
3. Wire the Thermolec Boiler, Pump & Thermostat
4. Flush, Fill & Purge then add Antifreeze
5. Turn it on and enjoy warm radiant floors!

Hydronic Radiant Center Includes:

- Thermolec Electric Boiler
- Circulating Pump
- Bladder Tank
- Pressure Temperature Gauge
- Air Eliminator
- Thick ABS Panel



Every Hydronic Radiant Center is factory leak tested and shipped fully assembled.



Model	kW	BTU/H	Max # of loops @ 300'	Max coverage area	Circuit Breaker Req	Panel Size
HRC-003-1-AX	3	10,239	2	600	20A	28"W x 35"H x 12"D
HRC-006-1-AX	6	20,478	4	1100	40A	28"W x 35"H x 12"D
HRC-009-1-AX	9	30,717	5	1600	50A	28"W x 35"H x 12"D
HRC-011-1-AX	11	37,543	7	2000	60A	28"W x 35"H x 12"D
HRC-015-1-AX	15	51,180	9	2700	80A	33"W x 36"H x 12"D
HRC-018-1-AX	18	61,416	11	3200	100A	33"W x 36"H x 12"D
HRC-023-1-AX	23	78,476	14	4100	125A	33"W x 36"H x 12"D

RMS/HRC 

Radiant Made Simple

75 W Veum Ave.
Appleton, MN 56208
(320) 297-9100

RADIANTMADESIMPLE.COM